

Claims

What we claim is:

1. A memory system comprising:
  - a memory comprising a plurality of dynamic memory cells, each cell storing a bit;
  - an access circuit connected to the memory to access, during an access cycle, a selected set of the bits stored in said memory cells;
  - an error detection circuit connected to the access circuit and said memory to detect an error in a bit accessed during said access cycle, comprising:
    - a first error detection circuit to detect an error in a bit of a first subset of said accessed bits; and
    - a second error detection circuit to detect an error in a bit of a second subset of said accessed bits.
2. The memory system of claim 1 wherein said first and second error detection circuits also correct said bit errors, respectively.
3. The memory system of claim 1 wherein said first and second subsets of said accessed bits are comprised of equal numbers of said bits.
4. The memory system of claim 1 wherein said first and second subsets of said accessed bits are comprised of different numbers of said bits.
5. The memory system of claim 1 wherein the memory system comprises an integrated circuit.

6. A memory system comprising:

a memory comprising first and second groups of dynamic memory cells,  
each cell storing a bit;

an access circuit connected to the memory to access, during an access cycle,  
a selected one of:

a first set of the bits stored in said first group of said memory cells; and

a second set of the bits stored in said second group of said memory  
cells;

an error detection circuit connected to the access circuit and said memory  
to detect an error in a bit accessed during said access cycle, comprising:

a first error detection circuit to detect an error in a bit of said first set of  
accessed bits; and

a second error detection circuit to detect an error in a bit of said second  
set of accessed bits.

7. The memory system of claim 6 wherein said first and second error  
detection circuits also correct said bit errors, respectively.

8. The memory system of claim 6 wherein said first and second subsets of  
said accessed bits are comprised of equal numbers of said bits.

9. The memory system of claim 6 wherein said first and second subsets of  
said accessed bits are comprised of different numbers of said bits.

10. The memory system of claim 6 further including:

a scrub circuit connected to the memory to scrub, during a scrub cycle, a  
selected one of:

said first set of the bits stored in said first group of said memory cells;

and

said second set of the bits stored in said second group of said memory cells.

11. The memory system of claim 10 wherein said access cycle and said scrub cycle are non-overlapping.
- 5 12. The memory system of claim 10 wherein said access cycle overlaps said scrub cycle, and wherein, during said access cycle, said access circuit accesses said selected one of said first and second sets of bits, and, during said scrub cycle, said scrub circuit scrubs the other of said selected first and second sets of bits.
- 10 13. The memory system of claim 10 wherein the memory system comprises an integrated circuit.

09334238 061699

- Sub  
ay
14. A memory system comprising:
- a memory comprising a plurality of dynamic memory cells arranged in a plane of rows and columns, each cell storing a bit;
  - an access circuit connected to the memory to access, during an access sequence, all of the bits stored in said plane of said memory cells;
  - an orthogonal error detection circuit connected to the access circuit and said memory to detect an error in a bit accessed during said access sequence, comprising:
    - a row error detection circuit to detect an error in a bit of a row of said accessed bits; and
    - a column error detection circuit to detect an error in a bit of a column of said accessed bits.
15. The memory system of claim 14 wherein said first and second error detection circuits also correct said bit errors, respectively.
16. The memory system of claim 14 wherein:
- said memory comprises a plurality of said planes of rows and columns of said memory cells, the corresponding memory cells of each plane forming respective stacks;
  - said access circuit accesses, during said access sequence, all of the bits stored in all of said planes of said memory cells; and
  - said orthogonal error detection circuit further comprises:
    - a stack error detection circuit to detect an error in a bit of a stack of said accessed bits.
17. The memory system of claim 16 wherein the stack error detection circuit comprises a parity check circuit.
18. The memory system of claim 16 wherein the stack error detection circuit comprises a RAEDAC unit.

19. The memory system of claim 14 wherein the column error detection circuit comprises a parity check circuit.
20. The memory system of claim 14 wherein the column error detection circuit comprises a RAEDAC unit.
- 5 21. The memory system of claim 14 wherein the row error detection circuit comprises a parity check circuit.
22. The memory system of claim 14 wherein the row error detection circuit comprises an EDAC unit.
23. The memory system of claim 14 wherein the memory system  
10 comprises an integrated circuit.

03/31/2010 10:16:59

24. A circuit for use in a memory system comprising:  
a memory comprising a plurality of dynamic memory cells arranged in a  
plane of rows and columns, each cell storing a bit;  
an access circuit connected to the memory to access, during an access  
sequence, all of the bits stored in said plane; and  
a row error detection circuit connected to the access circuit and said  
memory to detect an error in a bit of a row of said accessed bits;  
the circuit comprising:

a parity generation circuit connected to said memory to generate a parity  
bit related to all bits stored in a respective one of said columns.

25. The circuit of claim 24 further comprising:

a parity check circuit connected to said memory and to said parity  
generation circuit to detect an error in a bit of a column of said  
accessed bits using said parity bits.

26. The circuit of claim 25 further comprising:

an error correction circuit coupled to the memory and to the parity check  
circuit to correct said detected column bit error.

27. The circuit of claim 24 wherein the parity generation circuit generates a  
plurality of check bits, each related to a unique combination of at least two of  
said bits stored in a respective one of said columns.

28. The circuit of claim 27 further comprising:

an error detection circuit connected to said memory and to said parity  
generation circuit to detect an error in a bit of a column of said  
accessed bits using said parity bits.

29. The circuit of claim 28 further comprising:

an error correction circuit coupled to the memory and to the parity check circuit to correct said detected column bit error.

30. The circuit of claim 29 further characterized as an integrated circuit, random access error detection and correction (RAEDAC) unit.

09334238-061699  
669T90-8E24EE60

5

10

32. The RAEDAC of claim 31 wherein the error detection circuit detects multi-bit errors in said string using said parity bits.

add 27

**SECRET**